

Large Low-Stress Hand Stamps

SKU: **PPMS10140-PPMS27254**



COVID-19 NOTICE: PLEASE NOTE THAT ONLINE ORDERS MAY EXPERIENCE A DELAY BUT WILL BE DELIVERED AS SOON AS POSSIBLE

A range of large character size, low-stress number and letter hand stamps to permanently mark single characters by indenting. Sizes range from 14mm (5/64") to 25.4mm (1") character height.

Ministress low-stress engraving has a 'round face' which produces a continuous-line character. Ideal for applications which dictate lower stress levels are introduced into the component being marked, usually a requirement for aerospace, nuclear, oil and gas installations and military work.

- Use on aluminium to Stainless Steel, plastics, soft wood and some leathers up to a maximum hardness of 38 Rockwell C
- Hardened and tempered to precise limits
- Nickel plated
- 14mm (5/64") to 16mm (5/8") character heights can be used with an optional safety grip
- 19.05mm (3/4") and 25.4mm (1") character heights are supplied with rubber hand shroud.

All large-size hand stamps are manufactured to order in Sheffield, UK and have a two-week lead time

Smaller character sizes are stocked, find out more here

Overview

Best quality steel hand stamps made from chromium tool steel.

Round face engraving style to produce low-stress positive impressions; when you look at the engraved character on a standard hand stamp, the letter is a reflection /reverse of how it is indented.

All the stamps in this range are through hardened to between 58-62 Rockwell C and then tempered at the striking end to between 32-40 Rockwell C giving maximum safety in use.

Safety note: As with all striking tools, we recommend the use of appropriate safety protection. Safety glasses and gloves should be worn at all times

- 14mm to 16mm character heights are engraved on a hand stamp measuring 19.05mm square x 114.3mm long and can be used with an optional safety grip

Our Solutions



- Traceability Software & Data Capture
- Automated Part Marking
- Aerospace Marking Standards
- Automotive VIN Marking
- Hand Tools for Marking & Identification
- Serial Number Marking
- Logo Marking
- Production Data Monitoring

- 19.05mm (3/4") character height is engraved on a hand stamp measuring 35mm diameter, turned down to 22mm diameter x 165mm long, are supplied with a rubber hand shroud

- 25.4mm (1") character height is engraved on a hand stamp measuring 46mm diameter, turned down to 22mm diameter x 165mm long, are supplied with a rubber hand shroud.

Large character size hand stamps are supplied un-packed, with a protective coating on the engraved end, to be removed before use.

- Hardened and tempered to precise limits to give long life and maximum safety in use
- Nickel plated finish for rust protection and long product life
- Manufactured under stringent BS EN ISO 9001:2008 quality controls and exacting standards.



Products and Solutions available from Pryor



Traceability Software &
Data Capture



Automated Part
Marking



Aerospace Marking
Standards



Automotive VIN
Marking



Hand Tools for Marking
& Identification



Serial Number
Marking



Logo Marking



Production Data
Monitoring

Our Solutions

- Traceability Software & Data Capture
- Automated Part Marking
- Aerospace Marking Standards
- Automotive VIN Marking
- Hand Tools for Marking & Identification
- Serial Number Marking
- Logo Marking
- Production Data Monitoring